

WHAT YOU MOVE (PRIOR TO INSTALLATION)



- Remove all knick-knacks, disconnect and move all computers and electronic equipment (TV's, Stereos, Gaming Systems, etc.). Floors need to be clear, including closet floors.
- Removing any furniture/artwork and knick knicks along the path between the exterior door and the room the carpet is being installed so nothing is inadvertently knocked over or in the way (carpet rolls are large and awkward)



WHAT WE MOVE



- Gainesville Flooring can remove the furniture and set back in place and remove old flooring, which may result in dust being created.

PLEASE NOTE



- Installers try to avoid scratches/scuffs during installation, however, during installation process scratches to the paint on walls or baseboards may occur. It may be necessary for you to touch up your walls and baseboards, as it is an unexpected result of flooring installation.
- Depending on the floor thickness between old floors and new floors, the door jams may have a gap or affect the ability for a door to close after installation. Gainesville Flooring does not trim down doors, so you may have to hire a carpenter.
- Flooring installation creates dust, sometimes excessive dust, so it may require cleaning after our crews are finished.

CARPET



- Carpet rolls are heavy and awkward so the installers will need a spot outside to cut the carpet prior to bringing it inside...driveway, cul-de-sac or garage.
- Remove any knick-knacks or things along the path to the room where you are having carpet installed to prevent an accident.
- In order to properly stretch your carpet, the carpet backing may scratch the paint on the baseboards. Touching up your baseboards may be necessary as it is an expected result of carpet installation.
- If the carpet thickness affects the ability for a door to close after installation, Gainesville Flooring does not trim doors, so you may have to hire a carpenter.



TILE



- We use the Schluter shower systems for all shower installations which provides a patented, waterproof underlayment before the first tile is installed.
- The tile may need to be cleaned a couple days after installation due to a haze left as a result of the grouting process.
- Keep the traffic to a minimum during the first 24 hours to allow the thin set and grout to harden.